

# सीमा श्ल्क (निवारक) के आयुक्त का कार्यालय

# OFFICE OF THE COMMISSIONER OF CUSTOMS (PREVENTIVE) COMMISSIONERATE

, 3-17-55 सी 2 , 14- तल , औद्योगिक एस्टेट ,ऑटो नगर , विजयवाड़ा520,007 -

फोन 2551261-0866 :फैक्स2551156-0866 :

55-17-3, C-14, 2<sup>nd</sup> Floor, Industrial Estate, Autonagar, Vijayawada – 520007

Phone: 0866-2551261 Fax: 0866-2551156

C.No. I/7/02/2017- Admn

Dated 09.03.2017

## **TENDER NOTICE**

# TENDER NOTICE INVITING QUOTATIONS FOR PURCHASE OF LOGITECH CAMERAS)

Sealed tenders are invited from well reputed firms / vendors, manufacturers / authorized dealers / retailers for purchase of Logitech Cameras as per the following specifications for installation in the Offices of Customs Preventive Commissionerate, Vijayawada located all over Andhra Pradesh State.

Sl.No	Name of the Item	Description	Quan tity
1	HD Camera:	LOCATIONS: SGCPs: SRIKAKULAM, NARSAPUR, MACHILIPATNAM, SULLURPET, NELLORE CPDs: ONGOLE, VISAKHAPATNAM, KAKINADA Custom Houses/ICD: KAKINADA, KRISHNAPATNAM & GUNTUR (Marripalem) one for each location  Brand: Logitech BCC950	11
		Technical Specifications	
		Camera:  Motorized pan, tilt and zoom Integrated full duplex omni-directional speakerphone with 8- foot range On-board UVC H.264 encoding USB video class (UVC) supported applications Full HD 1080p 30fps video calling Camera and speakerphone controls, speakerphone and remote control Pan, tilt and zoom, Volume, Audio mute, Answer/Hang up Autofocus ZEISS lens certification 78-degree field of view 180-degree pan, 55-degree tilt Speaker: Bandwidth: 220 Hz - 20 kHz Max Output Level: 80 dB SPL @ 1 foot (0.30 meter) Microphone:	
		Bandwidth: 200 Hz - 8 kHz General:	

3.5mm analog headset jack 3 m (10-foot) range remote control USB 2.0 compiliant 2.4 m (8-foot) USB cable 2.4 m (8-foot) universal power adapter (228 mm) 9-inch extender stem for elevation / eye-level camera angle Windows* 7, 8.1, or 10 and Mac OS X 10.7 or higher  The above item shall be compatible with NIC software for Video Conference  2 HD CAMERA  FOR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 pan 130-degree field of view, Full HD 1080p 30 fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: -5% from 200Hz Kensington security slot Hub / Cable:				
USB 2.0 compliant 2.4 m (8-foot) USB cable 2.4 m (8-foot) universal power adapter (228 mm) 9-inch extender stem for elevation / eye-level camera angle Windows* 7, 8.1, or 10 and Mac OS X 10.7 or higher The above item shall be compatible with NIC software for Video Conference  FOR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			3.5mm analog headset jack	
2.4 m (8-foot) USB cable 2.4 m (8-foot) universal power adapter (228 mm) 9-inch extender stem for elevation / eye-level camera angle Windows® 7, 8.1, or 10 and Mac OS X 10.7 or higher The above item shall be compatible with NIC software for Video Conference  POR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: -5% from 200Hz Kensington security slot			3 m (10-foot) range remote control	
2.4 m (8-foot) universal power adapter (228 mm) 9-inch extender stem for elevation / eye-level camera angle Windows® 7, 8.1, or 10 and Mac OS X 10.7 or higher The above item shall be compatible with NIC software for Video Conference  FOR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Blu			USB 2.0 compliant	
(228 mm) 9-inch extender stem for elevation / eye-level camera angle Windows® 7, 8.1, or 10 and Mac OS X 10.7 or higher The above item shall be compatible with NIC software for Video Conference  POR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			2.4 m (8-foot) USB cable	
(228 mm) 9-inch extender stem for elevation / eye-level camera angle Windows® 7, 8.1, or 10 and Mac OS X 10.7 or higher The above item shall be compatible with NIC software for Video Conference  POR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30 fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			2.4 m (8-foot) universal power adapter	
camera angle Windows® 7, 8.1, or 10 and Mac OS X 10.7 or higher  The above item shall be compatible with NIC software for Video Conference  POR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth — plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz — 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
Windows® 7, 8.1, or 10 and Mac OS X 10.7 or higher The above item shall be compatible with NIC software for Video Conference  POR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth — plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
The above item shall be compatible with NIC software for Video Conference  FOR HQRS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 °pan 130-degree filt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call answer/end, volume and mute, Sluetooth Touch controls for call an				
Conference  POR HORS OFFICE, Vijayawada Brand: Logitech GROUP Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth — plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz — 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			Williams 7, 6.1, or 10 and wac CO X 10.7 or higher	
POR HQRS OFFICE,Vijayawada Brand: Logitech GROUP Smooth motorized pan,Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt,10x lossless HD zoom 90-degree field of view,Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			The above item shall be compatible with NIC software for Video	
Brand: Logitech GROUP  Smooth motorized pan,Tilt and zoom Controlled from remote or console 260 °pan 130-degree tilt,10x lossless HD zoom 90-degree field of view,Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth — plus camera PTZ, "home" preset and far-end control Microphonies (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz — 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			Conference	
Brand: Logitech GROUP  Smooth motorized pan,Tilt and zoom Controlled from remote or console 260 pan 130-degree tilt,10x lossless HD zoom 90-degree field of view,Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth — plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz — 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot	0	LID CANAEDA	FOR HORS OFFICE Viinterrade	,
Smooth motorized pan, Tilt and zoom Controlled from remote or console 260 pan 130-degree tilt, 10x lossless HD zoom 90-degree field of view, Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot	2	HD CAIVIERA		1
Controlled from remote or console 260 pan 130-degree tilt,10x lossless HD zoom 90-degree field of view,Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20-foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
130-degree field of view,Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			•	
90-degree field of view,Full HD 1080p 30fps H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			·	
H.264 UVC 1.5 with Scalable Video Coding (SVC) Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
Autofocus 5 camera presets Far-end control (PTZ) of ConferenceCam product ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
Far-end control (PTZ) of ConferenceCam product ZEISS lens certification, Kensington security slot LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth — plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz — 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			<b>5</b> ,	
ZEISS lens certification,Kensington security slot LED to confirm video streaming,Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			·	
LED to confirm video streaming, Standard tripod thread Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20-foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			` '	
Remote control: Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			ZEISS lens certification, Kensington security slot	
Dockable 8.5 m/28-foot range Speakerphone: Full-duplex performance,Acoustic echo cancellation Noise reduction technology,Ultra-wideband audio Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			LED to confirm video streaming, Standard tripod thread	
Speakerphone: Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			Remote control:	
Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			Dockable 8.5 m/28-foot range	
Full-duplex performance, Acoustic echo cancellation Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			Speakerphone:	
Noise reduction technology, Ultra-wideband audio Bluetooth and NFC enabled, LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth  Touch controls for call answer/end, volume and mute, Bluetooth – plus camera  PTZ, "home" preset and far-end control  Microphones (Tx)  Four omni-directional microphones supporting 6 m/20-foot diameter range  Frequency response: 100Hz – 11KHz  Sensitivity: -28dB +/-3dB  Distortion: <5% from 200Hz  Kensington security slot			·	
Bluetooth and NFC enabled,LCD for caller ID, call duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20-foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
duration and other functional response LEDs for speakerphone streaming, mute, hold, and Bluetooth Touch controls for call answer/end, volume and mute, Bluetooth – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			33.	
LEDs for speakerphone streaming, mute, hold, and <i>Bluetooth</i> Touch controls for call answer/end, volume and mute, <i>Bluetooth</i> – plus camera  PTZ, "home" preset and far-end control  Microphones (Tx)  Four omni-directional microphones supporting 6 m/20-foot diameter range  Frequency response: 100Hz – 11KHz  Sensitivity: -28dB +/-3dB  Distortion: <5% from 200Hz  Kensington security slot				
and <i>Bluetooth</i> Touch controls for call answer/end, volume and mute, <i>Bluetooth</i> – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			·	
Touch controls for call answer/end, volume and mute, <i>Bluetooth</i> – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
mute, <i>Bluetooth</i> – plus camera PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
PTZ, "home" preset and far-end control Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			,	
Microphones (Tx) Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			•	
Four omni-directional microphones supporting 6 m/20- foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			•	
foot diameter range Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			. , ,	
Frequency response: 100Hz – 11KHz Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot				
Sensitivity: -28dB +/-3dB Distortion: <5% from 200Hz Kensington security slot			foot diameter range	
Distortion: <5% from 200Hz Kensington security slot			Frequency response: 100Hz – 11KHz	
Kensington security slot			Sensitivity: -28dB +/-3dB	
			Distortion: <5% from 200Hz	
Hub / Cable:			Kensington security slot	
			Hub / Cable:	
Central mountable hub for connection of all				
components				
Included adhesive solution for under-table mounting			·	
Two cables for connection between hub and camera/			G	
speakerphone (Length: 5m/16 ft)				
			, , ,	
One USB cable for connection to PC/Mac (Length: 2			· -	
m/6.6 ft)			,	
AC Power adapter (Length: 3 m/9.8 ft)			,	
Mount:				
Dual purpose mount for wall placement or for elevating			Dual purpose mount for wall placement or for elevating	

Camera on table

The above item shall be compatible with NIC software for Video
Conference

- All the Items shall be covered by warranty of minimum one year.
- All the above items shall be installed at respective locations by the Vendor.
- The above quantity is only tentative. The Department reserves the right to increase or decrease the actual quantity required.

The tender shall be 2 bid system. The Technical bids will be opened first. After screening of the technical bids, the technically qualified venders shall demonstrate the compatibility of the hardware with NIC software for video conference. The financial bids of qualified bidders only will be opened only after satisfactory demonstration. The terms and conditions, prescribed proforma in which information has to be given in technical bid and financial bid are enclosed as Annexures- A,B and C respectively.

The tender document containing 'Technical Bid' and 'Financial Bid' in separate envelopes, super -scribed "TENDER/QUOTATION FOR PURCHASE OF **LOGITECH Cameras** complete in all respect should be addressed to the Asst. Commissioner (Admn), Customs Preventive Commissionerate (CPC), D.No.55-17-3, C-14, 2<sup>nd</sup> Road, Industrial Estate, Vijayawada -7 and sent to this office on or before 20.03.2017 by 17.00 hrs. The tender documents can be downloaded from the CBEC website - cbec.gov.in./Commissionerate website -apcustoms.gov.in. The interested vendors fulfilling the terms and conditions should quote their minimum rates along as mentioned in the tender document. Rate quoted by with **EMD of Rs.15**,000/the vendors will be valid for three months. All the vendors should also give brief resume about their firm/ company. Their turnover and firms / offices to which they are supplying quoted items, should also be mentioned. The Commissioner, Customs Preventive Commissionerate, Vijayawada reserves the right to reject all or any of the tenders without assigning any reason thereof. The tender which is conditional / incomplete/ belated/ without EMD, will not be entertained.

The last date for receipt of tender: 20.03.2017 by 17.00 p.m.

Technical Bid to be opened on : 21.03.2017 at 11.00 a.m.

Financial Bid to be opened on : 21.03.2017 at 14.00 p.m.

(G.S.MURALIDHAR)
ASSISTANT COMMISSIONER

#### <u> ANNEXURE – A</u>

#### **TERMS AND CONDITIONS**

The vendors are expected to examine all instructions, forms, terms and other information in the tender documents. Failure to furnish all information required as mentioned in the tender documents or submission of a proposal not substantially responsive to the tender documents in every respect will be at the vendor's risk and may result in rejection of the proposal and forfeiture of the bid.

- 1. The sealed cover containing quotations should be marked as "Quotation for Logitech Cameras".
- 2. Tender documents should be downloaded from CBEC website cbec.gov.in /apcustoms.gov.in as per the dates mentioned in the tender document.
- 3. Late submission will not be entertained. Last minute submission should be avoided as such the Commissioner, Customs Preventive Commissionerate, Vijayawada will not be responsible for late submission.
  - 4. Incomplete or conditional bids will be summarily rejected.
- 5. The Technical Bid and the Financial Bid as per Annexure B and Annexure C should be submitted.
- 6. The specifications of Hardware along with Brand/model etc. may be mentioned in the technical bid.
- 7. The price should not be mentioned in the Technical bid in any form or manner. In case the prices are mentioned in the technical bid, the offer will be liable for rejection.
  - 8. The technical bid and financial bid will be opened on specified dates.
- 9. The financial bid will be opened in respect of only those vendors whose documents are found in order and whose items qualify technically. The price comparisons in deciding lowest quotation for the complete value of all the items shall be made only over the rates quoted inclusive of all taxes. The lowest evaluated valid quotation will be selected.
- 10. The EMD of successful vendor will be converted into security till the complete supply is made and will be refunded without interest. The EMD of unsuccessful vendors will be returned after completion of the tender process.
- 11. The payment will be released after complete supply of material based on duly certified installation reports after installation are done.
- 12. The actual list of procurement of the goods will be given at the time of placing order.
- 13. The prices quoted shall be inclusive of all taxes of any government / local authority etc. as applicable to Govt. Department. No payment over and above the prices quoted shall be done.
- 14. The person signing the tender form ( or any other document forming part of the contract) on behalf of another, shall be deemed to warranty that he has the

authority to sign such documents and if an inquiry it appears that the person so signing had no authority to do so, the purchaser may without prejudice to other civil and criminal remedies against the contract, holds the signatory liable for all costs and damages and forfeiture of the earnest money.

- 15. The attempt on the part of the vendor, to negotiate directly or indirectly, with the authority to whom the tender is being submitted or with the tender accepting authority, before the finalization of tenders, will make vendor liable for exclusion from the consideration of his / her tender.
- 16. The delivery period would be 7 days from the date of issue of purchase order. For any delay in the supply of goods by the specified date, a liquidated damage of 0.5% of the delivered price of the delayed goods for each week or part thereof subject to a maximum limit of 10% of the delivered price of the delayed goods will be charged for the number of weeks or part thereof for which the camera(s) is supplied after the specified date given in the supply order.
- 17. If any disagreement or dispute arising between the vendor and the Government under or in connection with the terms and conditions, they shall make every effort to resolve amicably by direct informal negotiation, even then, if any disagreement or dispute arising between them shall be settled under the Court of Law within its jurisdiction at Vijayawada. The resultant contract will be interpreted under Indian Laws.

Signature of the Firm/Company with Seal

#### <u>ANNEXURE – B</u>

#### (TECHNICAL BID)

The Technical Bid should contain the following documents which must be attached with the technical bid.

- 2. The person signing the tender shall be deemed that he has the authority to sign the tender on behalf of the said company. Letter of authority to be attached.
- 3. Proof of Income Tax, Sales Tax, Service Tax and VAT Registration number ( as applicable) Self attested copies to be attached.
- 4. The product profile of the company along with last 3 years turnover, duly certified must be attached together with the list of reputed firms / offices to whom the company is supplying the tendered items.
- 5. The vendor should have a local presence, fully functional service with support staff to provide quality service support.
- 6. Proof of execution of supplied/executed in the last one year, to Government Department or Public Undertakings or reputed private sectors (within India). Proof of satisfactory service for the above mentioned purchases / works from the customer shall be attached. At least one customer in the Government Department or Public undertakings is a must.
- 7. The company / firm should be in existence and should have been in operation.
- 8. PAN No. of the company / firm, TIN No. ( as applicable) Self attested copies to be attached.
- 9. The bidder should not have any of their contracts terminated or blacklisted in the last three years by any State or Central Government / PSU / BFSI / Private Sector.
- 10. DD for Rs.15,000/- towards EMD drawn in favour of the Commissioner of Customs, Customs Preventive Commissionerate, Vijayawada.

Signature of the Firm/Company with Seal

## ANNEXURE - C

## (FINANCIAL BID)

Sl.No	Item	Make / Brand	Qty (In No.)	Rates per unit amount in (Rs.) inclusive of all taxes	Total Amount (Rs.)
Total amount (Rs.) (in Figure)					
Total amount (Rs.) (in words)					

#### Note:

- 1. The financial bid should contain the net rates to be charged on the basis of per unit.
- 2. The rates should be quoted in figures as well as in words, on the form attached as Annexure C and duly signed and stamped by the authorized persons
- 3. Rates mentioned above should be inclusive of all taxes, F.O.R. destination and installation charges and all other charges. No charges of whatsoever nature would be paid additional to the cost mentioned above.

Signature of the Firm/Company with Seal